




## Video Server Series

	Economy	Professional	
	VS-01Ae	VS-01Ap	WVS-01Ap
			
Image sensor	-	-	-
Sensor Size/Res	-	-	-
Shutter Speed	-	-	-
Max. Resolution	NTSC: 720x480 PAL: 720x576	NTSC: 720x480 PAL: 720x576	NTSC: 720x480 PAL: 720x576
Lens	No	No	No
Lens Mount	-	-	-
Focal Length	-	-	-
F value	-	-	-
View Angle   Horizontal	-	-	-
Auto Iris Support	-	-	-
Day & Night	-	-	-
Mechanical ICR	-	-	-
Infrared LED   Amount	-	-	-
Infrared LED   Distance	-	-	-
PIR/White LED	-	-	-
Video Compression/Frame Rate			
H.264 (fps@max. res.)	V(NTSC:30 fps / PAL:25 fps)	V(NTSC:30 fps / PAL:25 fps)	V(NTSC:30 fps / PAL:25 fps)
MPEG-4(fps@max. res.)	V(NTSC:30 fps / PAL:25 fps)	V(NTSC:30 fps / PAL:25 fps)	V(NTSC:30 fps / PAL:25 fps)
Motion JPEG(fps@max. res.)	V(NTSC:30 fps / PAL:25 fps)	V(NTSC:30 fps / PAL:25 fps)	V(NTSC:30 fps / PAL:25 fps)
Audio			
Audio Steaming	2 way (Built-in mic)	2 way (Built-in mic)	2 way (Built-in mic)
Environment	Indoor	Indoor	Indoor
Vandal-Proof	-	-	-
Operating Temperature	0°C ~ 50°C (32°F ~122°F)	0°C ~ 50°C (32°F ~122°F)	0°C ~ 50°C (32°F ~122°F)
General			
Analog Video Out	V	V	V
Terminal Block	DI/DO, RS-485	DI/DO, RS-485	DI/DO, RS-485
Wireless	-	-	802.11 a/b/g/n Dual Band
Hardware WPS Button	-	-	V
Local storage	-	SD/SDHC Slot Max.32G	SD/SDHC Slot Max.32G
Power Input	DC 12V 1A 802.3af PoE	DC 12V 1A/AC24V 802.3af PoE	DC 12V 1A/AC24V 802.3af PoE
Others			
	Max. mic range: 10m	3D de-interlace, 3D noise reduction, Max. mic range: 10m	3D de-interlace, 3D noise reduction, Max. mic range: 10m