


Azure Ready WiFi-BLE IoT Module



ITM-2262-Azure

Simplify security with built-in controls –

Protect your workloads quickly with built-in controls and services in Azure across identity, data, networking, and apps.

Detect threats early with unique intelligence –

Identify new threats and respond quickly with services that are informed by real-time global cybersecurity intelligence delivered at cloud scale.

Increase Developer Velocity with open source on Azure – Being able to leverage open-source tools also allows us to operate faster.

Substantial savings compared to other clouds – Save big with Azure offers.


Free enterprise-grade cost management tools – Keep costs in control with sophisticated tools.

- Built-in 512KB ROM +160KB SRAM
- Filter capacitors and RF matching links
- Provides 2.4 GHz 802.11 b/g/n
- Bluetooth and Bluetooth Low Energy connectivity to the host MCU
- Comes with a PCB antenna
- The host MCU can be connected to the module through a UART interface. If the module is LTE module, the host MCU can be connected to network via LTE module.


General Specification

CPU	Embedded nuvoTon M482ZIDAE
Flash	8Mbit, SPI Flash
Memory	Built-in 512KB ROM +160KB SRAM
Function	2.4GHz WLAN + BLE 5.0
Wifi Standard	802.11b/g/n 1T1R
BLE Standard	Bluetooth 5.0 Low Energy
Antenna_Type	PCB Antenna IPEX Connector
Tx Power	802.11b: 18dBm 802.11g: 14dBm 802.11n: 14dBm BLE: 5dBm
Rx Sensitivity	802.11b: -88dBm (11Mbps) 802.11g: -73dBm (54Mbps) 802.11n: -69dBm (HT40,MCS7) BLE: -91dBm
I/O Interface	GPIO, PWM, UART, I2C, SPI, ADC,...
Security	WEP 64/128, WPA, WPA2, WPA3
Dimension	35mm(L)*19mm(W)*3.0(H) mm
Power Range	3.0VDC~3.6VDC

Dimension:



Application:



PIN Definition::

